

EASY Installation & Activation of Your DCA

Before you install the program, can you please ensure you have the following minimum system requirements: <u>Details on this can be found here</u>

Note: The program only needs to be installed on one machine that stays on all the time (usually the server). The minimum requirements are only for the machine the program will be installed on. This platform will only monitor networked print devices.

To activate your DCA please refer to the following instructions:

- 1. Download and install a copy of the DCA the link will be in email you just received.
- 2. Follow the instructions outlined during installation (it will prompt you to basically just press "Next" each time)
- 3. When you get asked to launch the program. Keep the Tick box ticked and Click Finish.
- 4. It will automatically shut down and then the little box below will appear. Click YES.

Start Service			
	The Printer DCA background service is not running, would you like to start this now?		
	NOTE: If you are unsure, please select 'Yes'		
	Yes No		

TO CONFIRM

Your 3 tabs should look like the below 3 pictures



V.44.1.30205				
File Tools Options Help green tick				
Status Communication Scan File Viewer				
Communication Method				
Server: https://axess.axessmps.com	Test			
Using URL: https://axess.axessmps.com/pfe_ws/Main.asmx				
None	Communication Settings			
 Use Windows proxy settings 	Web Service Timeout: 30 🚖 seconds			
Use custom proxy settings Server: Port:	Web Service Discovery: 5000 milliseconds			
Authentication	Enable Intelligent Update			
 Default 	Enable Remote Device Configuration			
Custom Load Current	· · · · · · · · · · · · · · · · · · ·			
Authentication Type: Basic -				
Usemame:				
Password:				
Domain:				
🔚 Save 🌼 Force Scan				

	UP		
🖤 v. 4.4.1.30205			
File Tools Options Help Status Communication Scan File Viewer Scan Profile Default	Add Delete		
General Advanced Local Ranges Default Range From Active Directory IP Range: IP Address: IP Address: Hostname: Add Exclude Scan List: 192.168.1.1-192.168.1.254 Remove Import Export Clear 	Scanning Options □ Enable Broadcast □ Enable PJL □ Enable Rapid Scan □ Network Devices □ Local Devices Scan Interval: 60 • minutes Network Timeout: 5000 • milliseconds Local Agent Timeout: 30000 • milliseconds SNMP Retries: 5 • • Estimated Network Device scan time: 10 seconds Estimated Local Device scan time: 2 seconds		
should have IP addresses here			
E Save 🌼 Force Scan			

You should be done.

Please email your QPC representative to advise you have installed it so we can check and verify it has worked on our end.

Thank you!